

AT 119 - Spécifications techniques



Description

AT 119 tant pour les applications ATV/VTT que pour les prés et jardins. Le dessin de la bande de roulement assure une protection du champ excellente.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Véhicule ATV • Faucheuse

Version	STANDARD
Type	TL
Tyre Size	AT 22 X 11 - 8

Dimensions International Standard

Ply Rating	4
Section Width (mm)	280
Overall Diameter (mm)	580
Rim Rec	9.0 AT
Rim Alt	8.5 AT
ECE	E11-75R-004672

Load capacity (Kg)

km/h / bar	0.35
100	155

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 10:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..