

AW 09 - Spécifications techniques



Description

AW 09 a été conçu pour le labour du sol, la récolte de foin et les applications de transport avec des outils agricoles, les presses à paille et remorques. Il convient pour être utilisé dans l'agriculture moderne tant sur route que hors route. La carcasse renforcée garantit une capacité de charge élevée et une vie opérationnelle plus longue. AW 09 a été conçu avec un mélange particulièrement résistant aux coupures et déchirures en offrant une résistance excellente aux chaumes.

UM

International Standard

Construction

✚ BIAS

Machinery

Agriculture: Presse à paille • Moissonneuse • Outillage agricole • Remorque

Version	STANDARD
Type	TL
Tyre Size	260/70 - 15.3
LI/SS DRIVE WHEEL	110 A8
LI/SS FREE ROLLING	122 A8

Dimensions International Standard

Section Width (mm)	268
Overall Diameter (mm)	753
Static Loaded Radius (mm)	335
Rolling Circumference (mm)	2206
Rim Rec	9.00
ECE	E4-106R-000372

Load capacity (Kg)

km/h / bar	3.20
10 FR	2100
25 FR	1785
30 FR	1680
40 FR	1500
10 DW	1485
25 DW	1260
30 DW	1185
40 DW	1060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..