

AW 09 - Spécifications techniques



Description

AW 09 a été conçu pour le labour du sol, la récolte de foin et les applications de transport avec des outils agricoles, les presses à paille et remorques. Il convient pour être utilisé dans l'agriculture moderne tant sur route que hors route. La carcasse renforcée garantit une capacité de charge élevée et une vie opérationnelle plus longue. AW 09 a été conçu avec un mélange particulièrement résistant aux coupures et déchirures en offrant une résistance excellente aux chaumes.

UM

International Standard

Construction

❖ BIAS

Machinery

Agriculture: Presse à paille • Moissonneuse • Outillage agricole • Remorque

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS DRIVE WHEEL	132 A8
LI/SS FREE ROLLING	145 A8

Dimensions International Standard

Section Width (mm)	404
Overall Diameter (mm)	874
Static Loaded Radius (mm)	382
Rolling Circumference (mm)	2561
Rim Rec	AG 13.00
ECE	E4-106R-000381

Load capacity (Kg)

km/h / bar	3.60
10 FR	4060
25 FR	3450
30 FR	3250
40 FR	2900
10 DW	2800
25 DW	2380
30 DW	2240
40 DW	2000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..