

AW 702 - Spécifications techniques



Description

AW 702 a été conçu pour les outils agricoles, les remorques et les presses à paille dans les applications de travail de la terre et de transport. Ce pneu pour opérations pénibles a été développé par BKT pour offrir un nouveau degré de durabilité. AW 702 est disponible en différentes versions pour répondre aux exigences spécifiques des utilisateurs : une version « aramid belted » avec ceintures en aramide pour garantir une résistance exceptionnelle aux crevaisons, une version « HD » avec un mélange particulièrement résistant aux coupures et déchirures et une version « special » particulièrement résistant aux chaumes.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Outillage agricole • Remorque
Industriel: Remorque

Version	STANDARD
Type	TL
Tyre Size	7.00 - 12
LI/SS FREE ROLLING	95 A8

Dimensions International Standard

Ply Rating	6
Section Width (mm)	185
Overall Diameter (mm)	665
Static Loaded Radius (mm)	295
Rolling Circumference (mm)	1948
Rim Rec	4.25
ECE	E4-106R-001957

Load capacity (Kg)

km/h / bar	2.50
10 FR	965
25 FR	820
30 FR	775
40 FR	690

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 06:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..