

AW 708 - Spécifications techniques

Description

AW 708 a été conçu pour le travail de la terre et les applications de transport et récolte du foin avec les outils agricoles, remorques et presses à paille. Une version « HD » est disponible avec un mélange particulièrement résistant aux coupures et déchirures.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Outillage agricole • Remorque
Industriel: Remorque



Version	STANDARD
Type	TL
Tyre Size	500/65 - 17
LI/SS FREE ROLLING	160 A8

Dimensions International Standard

Ply Rating	18
Section Width (mm)	525
Overall Diameter (mm)	1080
Static Loaded Radius (mm)	462
Rolling Circumference (mm)	3135
Rim Rec	16.0
ECE	E11-106R-004549

Load capacity (Kg)

km/h / bar	3.50
10 FR	6300
25 FR	5355
30 FR	5040
40 FR	4500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 12:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..