

AW 711 - Spécifications techniques



Description

AW 711 est un pneu radial pour les outils agricoles, spécialement conçu pour être utilisé dans l'agriculture moderne et convenant pour des applications de transport, le récolte du foin e le travail de la terre. Grâce au mélange spécial de la bande de roulement, AW 711 assure une longue durée de vie du produit, qu'il soit utilisé sur des surfaces souples ou dures. La faible résistance au roulement pendant le transfert sur route permet de réaliser d'importantes économies quant à la consommation de carburant. Grâce à la technologie VF, AW 711 garantit une capacité de charge élevée à de basses pressions.

UM

International Standard

Construction



RADIAL

Machinery

Agriculture: Moissonneuse • Outillage agricole

Version	STEEL BELTED
Type	TL
Tyre Size	VF 480/45 R 17
LI/SS	167 A8/B

Dimensions International Standard

Section Width (mm)	491
Overall Diameter (mm)	866
Static Loaded Radius (mm)	363
Rolling Circumference (mm)	2644
SRI (mm)	410
Rim Rec	16.00
ECE	E4-106R-002652

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
From 10 to 50 km/h	1585	2020	2455	2780	3220	3655	4035	4415	4855	5450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 10:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..