

## AW 726 - Spécifications techniques



### Description

AW 726 a été particulièrement conçu pour les remorques dans les applications de transport. Ce pneu est approprié tant pour une utilisation sur route que hors route. AW 726 assure de bonnes performances sur route ainsi que d'excellentes qualités d'auto-nettoyage. Le dessin à blocs garantit un cycle de vie plus long.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Remorque

Version	STANDARD
Type	TL
Tyre Size	420/55 - 17
LI/SS DRIVE WHEEL	121 A8
LI/SS FREE ROLLING	133 A8

## Dimensions US Standard

Usa code	94055647
Section Width (inch)	16.3
Overall Diameter (inch)	35
Static Loaded Radius (inch)	15.4
Rolling Circumference (inch)	101.7
Rim Rec	13.00
ECE	E11-106R-005265

## Load capacity (lbs)

mph / psi	29
5 FR	6360
15 FR	5400
20 FR	5080
25 FR	4540
5 DW	4480
15 DW	3800
20 DW	3580
25 DW	3200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 12:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..