

BK 208 - Spécifications techniques



Description

BK 208 convient pour les applications avec remorques et camionnettes. C'est un pneu d'une durabilité et fiabilité remarquables pour les utilisations tant aux champs que sur la route.

UM

US Standard

Construction

✚ BIAS

Machinery

Agriculture: Tracteur compact • Camion léger • Remorque

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

Dimensions US Standard

Usa code	94013241
Ply Rating	14
Section Width (inch)	8.3
Overall Diameter (inch)	31.9
Rim Rec	6.00 G

Load capacity (lbs)

	mph / psi	-
-	-	-
-	-	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 05:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..