

BK-LOADER 53 - Fiche de données



Description

BK-LOADER 53 est un pneu avec ceintures en aramide, développé pour les chargeurs dans les applications industrielles. Le dessin exclusif de la bande de roulement extra-profonde garantit une excellente stabilité latérale ainsi qu'une extraordinaire résistance à l'usure, aux coupures et aux crevaisons. BK-LOADER 53 se distingue par d'exceptionnelles propriétés d'autonettoyage, et par une traction et une adhérence optimales sur surfaces mouillées et sèches. Ce pneu est particulièrement adapté pour les opérations de recyclage.

UM

International Standard

Construction



RADIAL

Machinery

Industriel: Chargeur

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type
365/70 R 18	ARAMID BELTED	146A2/142A4	11		360	990	458	3017		TL
405/70 R 18	ARAMID BELTED	153A2/149A4	13	14 ; 13 SDC; 12 ;12 SDC	407	1045				TL
405/70 R 20	ARAMID BELTED	155A2/151A4	13	14 ; 13 SDC; 12 ;12 SDC	407	1097	511	3339	525	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 03:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..