



## BOGMAX - Fiche de données



### Description

BOGMAX a été particulièrement conçu pour les applications pour tous les types de terrain. Le dessin très profond de la bande de roulement garantit une excellente traction, tandis que les bourrelets de protection du flanc atténuent les chocs et les dommages éventuels. BOGMAX est un pneu à 6 plis avec la technologie M+S – idéal pour performances dans le sport en toute condition.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Agriculture: Véhicule ATV

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type
<b>AT 30 X 10 - 14</b>	STANDARD	58 F	6	7.0 AT	7.5 AT ; 8.0 AT	260	760	TL
<b>AT 32 X 10 - 14</b>	STANDARD	62 F	6	8.0 AT	8.5 AT	250	810	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 10:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..