

COLT - Spécifications techniques



Description

COLT est un pneu dont le dessin de la bande de roulement est à blocs, il convient pour le transport avec remorques et camionnettes aux champs et sur la route. COLT garantit une plus grande durabilité et des performances élevées pendant tout le cycle de vie du produit.

UM

International Standard

Construction

✚ BIAS

Machinery

Agriculture: Camion léger • Remorque

Industriel: Remorque

Version	STANDARD
Type	TT
Tyre Size	7.50 - 15

Dimensions International Standard

Ply Rating	14
Section Width (mm)	217
Overall Diameter (mm)	790
Rim Rec	6.00

Load capacity (Kg)

km/h / bar	6.50
100 LS	1450
100 LD	1375

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 15:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..