

# COMMANDER 3 RIB - Spécifications techniques



## Description

COMMANDER 3 RIB est un pneu avant avec nervure de la bande de roulement à 3 côtes adapté pour les applications de travail de la terre et de transport. Il offre excellentes durabilité et capacité de charge, grâce à une répartition des poids optimisée sur les côtes dans la partie centrale et dans la zone de l'épaule. La carcasse robuste et le mélange résistant à tous les types de coupure assurent une excellente résistance aux crevaisons.

## UM

US Standard

## Construction

❖ BIAS

## Machinery

Agriculture: Tracteur 2WD

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16
LI/SS	99 A8

## Dimensions US Standard

Usa code	8903094076284
Ply Rating	8
Section Width (inch)	8.3
Overall Diameter (inch)	31.9
Rim Rec	5.50 F
Rim Alt	5.00 F ; 5 K ; 6.00 F
TRA Code	F2

## Load capacity (lbs)

mph / psi	56
25	1710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 16:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..