

D 404 - Spécifications techniques



Description

D 404 est un pneu qui trouve son utilisation essentiellement sur la route et il est idéal pour les applications avec remorques et camionnettes. Son adhérence exceptionnelle sur la route, associée à une usure régulière, se traduit par une durabilité élevée.

UM

International Standard

Construction

✚ BIAS

Machinery

Agriculture: Camion léger • Remorque

Version	STANDARD
Type	TT
Tyre Size	8.25 - 16

Dimensions International Standard

Ply Rating	18
Section Width (mm)	238
Overall Diameter (mm)	858
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E4-54R-0024097

Load capacity (Kg)

km/h / bar	7.95
100 LS	1900
100 LD	1800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 11:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..