

DESERT KING - Fiche de données



Description

Le DESERT KING est le mieux adapté aux sols meubles, aux terrains sablonneux et aux finisseurs avec des « desert trucks ». La conception optimisée de la bande de roulement à nervures offre une flottaison et une stabilité directionnelle excellentes. Sa carcasse en nylon robuste et son talent très résistant sont spécialement conçus pour des conditions d'utilisation à basse pression. Le DESERT KING offre également une résistance élevée aux perforations et une durée de vie prolongée du pneu.

UM

US Standard

Construction

❖ BIAS

Machinery

OTR: Desert Truck

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	Tread Depth
18.00 - 25 DT	STANDARD	94069743	E7	16	10.00/1.5		18.5	60.4	25	173.4	TL	20
21.00 - 25 DT	STANDARD	94067633	E7	16	15.00/3.0		22.4	65.4	27.9	193.1	TL	22
29.5 - 25 DT	STANDARD	94069057	E7	28	25.00/3.5		30.3	71.7	30.9	212.3	TL	26

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 11:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..