

EARTHMAX CRUSHER HAUL - Spécifications techniques



Description

EARTHMAX CRUSHER HAUL est un pneu radial All Steel conçu pour les applications de transport sur route que hors route, ainsi que les opérations dans les mines. Le pneu offre une plus grande durabilité et un kilométrage supérieur. La robuste construction et carcasse avec des ceintures d'acier garantit une capacité de charge élevée. Le dessin de la bande de roulement à blocs assure une excellente traction. En route, EARTHMAX CRUSHER HAUL offre un confort de conduite extraordinaire, un niveau de manœuvrabilité élevé, ainsi que moins de fatigue pour le conducteur.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Camion à benne basculante

Version	STANDARD
Type	TT
Tyre Size	11.00 R 20
LI/SS	152/149 J

Dimensions US Standard

Usa code	94070565
Ply Rating	18
Overall Width (inch)	11.4
Overall Diameter (inch)	43.4
Rim Rec	8.00
Rim Alt	8.50
Tread Depth	25

Load capacity (lbs)

mph / psi	120
62 Load Single	7825
62 Load Dual	7165

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/05/2025 14:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..