

EARTHMAX SR 23 - Fiche de données



Description

EARTHMAX SR 23 (G-2/L-2) est un pneu radial All Steel (Tout Acier) particulièrement conçu pour les niveleuses et chargeuses. Il se distingue de par une excellente traction antérieure et latérale ainsi que par une capacité d'auto-nettoyage exceptionnelle. La carcasse robuste et la bande de roulement particulièrement résistante aux coupures lui assurent un long cycle de vie.

UM

International Standard

Construction



RADIAL

Machinery

OTR: Niveleuse • Chargeur

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
15.5 R 25	CUT RESISTANT COMPOUND	G2/L2	*	146 A8/169 A2	12.00/1.3		383	1264	559	3756	TL	27
17.5 R 25	CUT RESISTANT COMPOUND	G2/L2	*	153 A8/176 A2	14.00/1.5		448	1345	612	4108	TL	27
20.5 R 25	CUT RESISTANT COMPOUND	G2/L2	*	161 A8/186 A2	17.00/2.0		535	1490	668	4489	TL	31

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 11:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..