

## EARTHMAX SR 32 - Spécifications techniques



### Description

EARTHMAX SR 32 est un pneu radial large non directionnel adapté pour les décapeuses. Ce pneu est caractérisé par une carcasse robuste All Steel et par un mélange spécial qui garantissent une résistance aux coupures et crevaisons ainsi que durabilité excellentes. Les autres avantages sont traction et flottaison extraordinaires même dans les conditions de service les plus sévères.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Décapeuse

|           |                        |
|-----------|------------------------|
| Version   | CUT RESISTANT COMPOUND |
| Type      | TL                     |
| Tyre Size | 33.25 R 29             |
| LI/SS     | 209 B                  |

## Dimensions International Standard

|                            |           |
|----------------------------|-----------|
| TKPH                       | 346       |
| Overall Width (mm)         | 845       |
| Overall Diameter (mm)      | 2080      |
| Static Loaded Radius (mm)  | 915       |
| Rolling Circumference (mm) | 6250      |
| Rim Rec                    | 27.00/3.5 |
| Rim Alt                    | 26.00/3.5 |
| Star Rating                | **        |
| TRA Code                   | E3        |
| Tread Depth                | 54        |

## Load capacity (Kg)

|            |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|
| km/h / bar | 4.00  | 4.25  | 4.50  | 4.75  | 5.00  | 5.25  |
| 50         | 15000 | 15500 | 16500 | 17000 | 17500 | 18500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 14:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..