

EARTHMAX SR 33 - Spécifications techniques



Description

Earthmax SR 33 est un pneu radial pour véhicules polyvalents. Le dessin particulier à blocs a été conçu pour assurer une excellente traction sur les surfaces molles, sablonneuses ou boueuses. Earthmax SR 33 offre une excellente stabilité ainsi que des propriétés d'auto-nettoyage exceptionnelles. La carcasse All Steel (Tout Acier) se distingue de par une excellente durabilité et une grande résistance aux coupures et crevaisons.

UM

US Standard

Construction

 RADIAL

Machinery

Industriel: Véhicule universel

Version	STANDARD
Type	TL
Tyre Size	395/85 R 20
LI/SS	168 J

Dimensions US Standard

Usa code	94050611
Overall Width (inch)	15.5
Overall Diameter (inch)	46.6
Static Loaded Radius (inch)	21.2
Rolling Circumference (inch)	141.3
Rim Rec	10.00W
Rim Alt	10.00HF
ECE	E11-54R-0017315

Load capacity (lbs)

mph / psi	125
62	12300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 11:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..