

EARTHMAX SR 412 - Spécifications techniques



Description

EARTHMAX SR 412 (E-4/L-4) est un pneu radial All Steel (Tout Acier) spécialement conçu pour les tombereaux articulés, les chargeurs et les bulldozers. Le dessin unique de la bande de roulement d'une profondeur E-4 assure une excellente traction et une résistance particulière à la chaleur. Grâce à la carcasse et les ceintures All Steel, EARTHMAX SR 412 permet de transporter des charges lourdes, en offrant une excellente stabilité et une résistance exceptionnelle aux déchirures et crevaisons. EARTHMAX SR 412 est réalisé avec une épaule en forme de carré qui assure un contact optimal avec le terrain et une manœuvrabilité exceptionnelle.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Tombereau articulé • Bulldozer • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	750/65 R 25 (30/65 R 25)
LI/SS	190 B/202 A2

Dimensions US Standard

Usa code	94065233
TMPH	157
Overall Width (inch)	30.7
Overall Diameter (inch)	63.1
Static Loaded Radius (inch)	28.1
Rolling Circumference (inch)	190.5
Rim Rec	24.00/3.0
Rim Alt	22.00/3.0, 25.00/3.0
Star Rating	**/*
TRA Code	E4/L4
Tread Depth	69

Load capacity (lbs)

mph / psi	58	62	65	69
30	20900	21500	22700	23400
5	29100	30900	32000	33100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 06:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..