

# EARTHMAX SR 41 - Spécifications techniques



## Description

EARTHMAX SR 41 est un pneu radial All Steel (Tout Acier) pour les camions à benne articulée, les chargeurs et les bulldozers. Grâce à sa structure All Steel (Tout Acier) et à son dessin à blocs, EARTHMAX SR 41 offre une excellente résistance aux crevaisons et une plus longue durée de vie. Non seulement ce pneu permet d'effectuer de nombreuses heures de travail sans immobilisation, mais il offre de plus un confort formidable. EARTHMAX SR 41 est également disponible en SH-4\*\*\*\* pour les camions à benne basculante à profil bas (LPDT) utilisés dans les opérations de transport souterrain.

## UM

US Standard

## Construction



## Machinery

OTR: Tombereau articulé • Bulldozer • Chargeur •  
Tombereau surbaissé

|           |                        |
|-----------|------------------------|
| Version   | CUT RESISTANT COMPOUND |
| Type      | TL                     |
| Tyre Size | 23.5 R 25              |
| LI/SS     | 185 B/195 A2           |

## Dimensions US Standard

|                              |           |
|------------------------------|-----------|
| Usa code                     | 94053353  |
| TMPH                         | 110       |
| Overall Width (inch)         | 24.2      |
| Overall Diameter (inch)      | 63.4      |
| Static Loaded Radius (inch)  | 28.5      |
| Rolling Circumference (inch) | 188.6     |
| Rim Rec                      | 19.50/2.5 |
| Star Rating                  | **/*      |
| TRA Code                     | E4/L4     |
| Tread Depth                  | 67        |

## Load capacity (lbs)

| mph / psi | 58    | 62    | 65    | 69    | 73    | 76    |
|-----------|-------|-------|-------|-------|-------|-------|
| 30        | 16500 | 17100 | 18200 | 18700 | 19800 | 20400 |
| 5         | 22700 | 23400 | 24700 | 25400 | 26800 | -     |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 11:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..