

EARTHMAX SR 425 - Fiche de données



Description

EARTHMAX SR 425 est un pneu radial All Steel conçu pour les applications de transport sur route que hors route, ainsi que les opérations dans les mines. Le pneu offre une plus grande durabilité et un kilométrage supérieur. La robuste construction et carcasse avec des ceintures d'acier garantit une capacité de charge élevée. Le dessin de la bande de roulement à blocs assure une excellente traction. En route, EARTHMAX SR 425 offre un confort de conduite extraordinaire, un niveau de manœuvrabilité élevé, ainsi que moins de fatigue pour le conducteur.

UM

International Standard

Construction

RADIAL

Machinery

OTR: Camion à benne basculante

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
12.00 R 24	STANDARD	160/156 K	8.50	9.00	310	1230	564	3785	TL	21
12.00 R 24	STANDARD	160/156 K	8.50	9.00	310	1230	564	3785	TT	21

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/05/2025 10:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..