



## EARTHMAX SR 42 - Fiche de données



### Description

EARTHMAX SR 42 est un pneu radial OTR particulièrement conçu pour les trains routiers dans les mines "haul train" et les applications lourdes pour le transport de bois. Le dessin caractéristique de la bande de roulement assure d'excellentes traction et stabilité latérale ainsi que des performances exceptionnelles de freinage et de comportement dans les virages sur terrains accidentés ou sur graviers même en présence de neige ou verglas. En effet, le mélange de la bande de roulement, particulièrement résistant aux coupures et à l'usure, est parfaitement adapté aux conditions climatiques extrêmement froides. EARTHMAX SR 42 présente une carcasse All Steel (Tout Acier) qui garantit une solidité exceptionnelle et un long cycle de vie.

### UM

US Standard

### Construction

RADIAL

### Machinery

OTR: Haul Train

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth	TMPH
14.00 R 24	CUT RESISTANT COMPOUND	94067138	E4	***	171 B	10.00W	--	15	55.6	25.7	166.6	TL	48	72
14.00 R 25	CUT RESISTANT COMPOUND	94048984	E4	***	171 B	10.00/1.5	--	15	55.6	25.7	166.6	TL	48	72
14.00 R 25	CUT RESISTANT COMPOUND	94067190	E4	***	171 B	10.00/2.0	--	15	55.6	25.7	166.6	TL	48	72

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 15:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..