

EARTHMAX SR 46 - Spécifications techniques



Description

Earthmax SR 46 pour tombereaux rigides apporte une réponse novatrice aux milieux rocheux, abrasifs et hostiles des mines. Ce pneu a été particulièrement conçu pour le transport de charges lourdes et il offre une résistance exceptionnelle aux coupures et déchirures et permet donc un cycle de vie plus long du produit. La carcasse et les ceintures All Steel (Tout Acier) assurent une protection extraordinaire contre les coups, sollicitations et crevaisons afin de maximiser les heures de travail et donc augmenter la productivité. Earthmax SR 46 est caractérisé par un dessin spécial de la bande de roulement qui est dotée de crampons à blocs avec rainurage le long de la circonférence. Ceci confère donc d'excellentes performances dans les virages avec un minimum de dommages sur la partie externe de la bande de roulement.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Tombereau rigide

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	30.00 R 51
LI/SS	230 B

Dimensions International Standard

TKPH	500
Overall Width (mm)	835
Overall Diameter (mm)	2895
Static Loaded Radius (mm)	1300
Rolling Circumference (mm)	8800
Rim Rec	22.00/4.5
Star Rating	**
TRA Code	E4
Tread Depth	77

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	25750	26500	28000	29000	30000	30750	31500	32500	33500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/05/2025 09:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..