

EARTHMAX SR 51 - Spécifications techniques



Description

EARTHMAX SR 51 (L-5) est un pneu radial **All Steel** (Tout Acier) particulièrement conçu pour les chargeuses et bulldozers. EARTHMAX SR 51 est idéal pour les opérations pénibles qui exigent une plus grande résistance aux coupures, une protection des flancs et une traction exceptionnelle.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Bulldozer • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	176 A2

Dimensions International Standard

Overall Width (mm)	437
Overall Diameter (mm)	1398
Static Loaded Radius (mm)	630
Rolling Circumference (mm)	4110
Rim Rec	14.00/1.5
Star Rating	*
TRA Code	L5
Tread Depth	61

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00
10	6000	6150	6500	6700	7100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 02:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..