

EARTHMAX SR 55 - Spécifications techniques



Description

EARTHMAX SR 55 (L-55) est un pneu radial All Steel (Tout Acier) spécialement conçu pour les chargeuses, les bulldozers et les chargeurs-transporteurs qui opèrent dans les conditions les plus pénibles, comme les carrières et les mines et les chantiers de démolition. Grâce au dessin de la bande de roulement extra profonde et lisse, EARTHMAX SR 55 est capable d'atteindre des niveaux de productivité élevés, avec des temps d'arrêt machine inférieurs. Les opérateurs des machines en apprécieront aussi stabilité et traction excellentes.

UM

International Standard

Construction



RADIAL

Machinery

OTR: Bulldozer • Chargeur-transporteur LHD • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	193 A2

Dimensions International Standard

Overall Width (mm)	535
Overall Diameter (mm)	1543
Static Loaded Radius (mm)	700
Rolling Circumference (mm)	4644
Rim Rec	17.00/2.0
Star Rating	**
TRA Code	L5S
Tread Depth	74

Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50
10	9750	10000	10300	10900	11200	11500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 08:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..