

EARTHMAX SR 57 - Spécifications techniques



Description

EARTHMAX SR 57 est un pneu radial All Steel (Tout Acier) particulièrement conçu pour les chargeurs, bulldozers et les véhicules utilitaires utilisées dans les mines souterraines. Ce pneu assure une traction supérieure, ainsi que stabilité et confort sur les terrains rugueux et rocheux. La bande de roulement extra profonde L-5, associée au mélange avec formule spéciale UMS (underground mine service), lui assure une résistance supérieure à l'usure ainsi qu'une excellente résistance contre les coupures dues aux rochers et les crevaisons.

UM

US Standard

Construction



RADIAL

Machinery

OTR: Bulldozer • Chargeur-transporteur LHD • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	18.00 R 25
LI/SS	204 A2

Dimensions US Standard

Usa code	94063307
Overall Width (inch)	20.3
Overall Diameter (inch)	65
Rim Rec	13.00/2.5
Star Rating	**
TRA Code	L5
Tread Depth	101

Load capacity (lbs)

mph / psi	83	87	91	94	98	102	105	109	112	116	120
5	26800	27600	28300	29100	30000	30900	32000	33100	33600	34200	35300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 17:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..