

## EARTHMAX SR LOADER - Fiche de données



### Description

EARTHMAX SR LOADER est un pneu OTR particulièrement conçu pour les opérations de chargement et nivellement, ainsi que pour les applications de transport avec tombereaux articulés. Sa carcasse All Steel (Tout Acier) renforcée par des ceintures en acier multicouche et le composé exclusif de la bande de roulement offrent une résistance exceptionnelle aux déchirures et crevaisons, ce qui se traduit par une durée de vie plus longue du pneu. EARTHMAX SR LOADER est doté d'un dessin exclusif de la bande de roulement qui assure d'excellentes propriétés d'auto-nettoyage et une traction optimale sur une large gamme de terrains.

### UM

International Standard

### Construction



RADIAL

### Machinery

OTR: Tombereau articulé • Bulldozer • Chargeur

| SIZE             | Version                | TRA Code | Star R | LI/SS        | RIM REC   | RIM ALT | OW  | OD   | SLR | RC   | Type | Tread Depth | TKPH |
|------------------|------------------------|----------|--------|--------------|-----------|---------|-----|------|-----|------|------|-------------|------|
| <b>20.5 R 25</b> | CUT RESISTANT COMPOUND | E3/L3    | **/*   | 177 B/186 A2 | 17.00/2.0 |         | 530 | 1475 | 649 | 4384 | TL   | 29          | 170  |
| <b>23.5 R 25</b> | CUT RESISTANT COMPOUND | E3/L3    | **/*   | 185 B/195 A2 | 19.50/2.5 | --      | 612 | 1605 | 706 | 4770 | TL   | 31          | 200  |
| <b>26.5 R 25</b> | CUT RESISTANT COMPOUND | E3/L3    | **/*   | 193 B/202 A2 | 22.00/3.0 |         | 681 | 1735 | 763 | 5179 | TL   | 34          | 230  |
| <b>29.5 R 25</b> | CUT RESISTANT COMPOUND | E3/L3    | **/*   | 200 B/208 A2 | 25.00/3.5 |         | 768 | 1859 | 818 | 5549 | TL   | 37          | 270  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 03:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..