

EM 938 - Spécifications techniques



Description

EM 938 a été spécialement conçu pour les excavatrices sur les chantiers de construction routière. Ce pneu a été réalisé avec un mélange spécial de la bande de roulement, particulièrement résistant aux coupures et déchirures, tandis que le dessin agressif de cette même bande de roulement assure une excellente traction. EM 938 se distingue de par ses propriétés extraordinaires d'auto-nettoyage. La carcasse robuste confère une résistance exceptionnelle aux chocs et secousses même lors des opérations de service pénible.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Pelleteuse

Version	STANDARD
Type	TT
Tyre Size	9.00 - 20

Dimensions International Standard

Ply Rating	16
Overall Width (mm)	256
Overall Diameter (mm)	1012
Static Loaded Radius (mm)	481
Rolling Circumference (mm)	3070
Rim Rec	7.0
Rim Alt	6.5 ; 7.5
TRA Code	E2

Load capacity (Kg)

km/h / bar	7.75
50	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 12:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..