



## F 240 - Fiche de données



### Description

F 240 est un pneu forestier particulièrement conçu pour la manutention des troncs. Le dessin de la bande de roulement assure une excellente traction, des propriétés d'autonettoyage optimales ainsi qu'une bonne manœuvrabilité. Le mélange de qualité supérieure de la bande de roulement garantit une extraordinaire résistance aux coupures et à l'usure, et donc une plus longue vie du pneu. F 240 est caractérisé par une large zone de contact, qui confère une plus grande stabilité.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Agriculture: Débusqueuse

| SIZE                               | Version  | USACode  | TRA Code | PR | RIM REC  | RIM ALT | SW   | OD   | SLR  | RC    | Type | ECE             |
|------------------------------------|----------|----------|----------|----|----------|---------|------|------|------|-------|------|-----------------|
| <b>18 - 15.5</b>                   | STANDARD | 94052004 | LS2      | 14 | AG 13.00 |         | 17.7 | 39   | 16.9 | 115.4 | TT   | E11-106R-004259 |
| <b>400 - 15.5<br/>(400 - 15.5)</b> | STANDARD | 94051588 | LS2      | 12 | AG 13.00 |         | 15.9 | 34.1 | 0    | 0     | TT   | E11-106R-004260 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 13:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..