

# FARM 2000 PLUS - Spécifications techniques



## Description

FARM 2000 PLUS est un pneu pour l'agriculture qui se distingue de par un grand nombre de pavés afin de garantir de meilleures performances dans les opérations aux champs et sur route. La bande de roulement profonde assure une longue vie du pneu, tandis que l'excellent mélange de la bande de roulement se traduit par une résistance exceptionnelle aux coupures et déchirures. FARM 2000 PLUS présente une capacité d'auto-nettoyage extraordinaire ainsi qu'un dessin particulier des angles des pavés, qui le rendent tout à fait adapté pour des applications aux champs et de transport.

## UM

International Standard

## Construction

❖ BIAS

## Machinery

Agriculture: Tracteur

Version	SPECIAL
Type	TT
Tyre Size	16.9 - 28
LI/SS	143 A6

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	440
Overall Diameter (mm)	1435
Static Loaded Radius (mm)	657
Rolling Circumference (mm)	4311
Rim Rec	W 15 L
Rim Alt	W 14 L
TRA Code	R1

## Load capacity (Kg)

km/h / bar	2.40
30	2725

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..