

# FARM HIGHWAY TOUGH - Spécifications techniques



## Description

FARM HIGHWAY TOUGH est un pneu à haute vitesse conçu pour les applications de transport et le labour du sol avec remorques et outils agricoles. Il offre une capacité de charge élevée même à grande vitesse et il assure une longue durée de vie du pneu.

## UM

International Standard

## Construction

✚ BIAS

## Machinery

Agriculture: Outillage agricole • Remorque

|           |              |
|-----------|--------------|
| Version   | STANDARD     |
| Type      | TL           |
| Tyre Size | 9.5L - 15 FI |

## Dimensions International Standard

|                            |      |
|----------------------------|------|
| Ply Rating                 | 8    |
| Section Width (mm)         | 245  |
| Overall Diameter (mm)      | 766  |
| Static Loaded Radius (mm)  | 343  |
| Rolling Circumference (mm) | 2183 |
| Rim Rec                    | 7.00 |
| Rim Alt                    | 8 LB |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 4.10 |
| 100        | 1215 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 21:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..