

FL 630 SUPER - Spécifications techniques



Description

FL 630 SUPER est un pneu Flotation particulièrement adapté pour les applications aux champs et sur route avec des remorques, camions-citernes et épandeurs. Sa structure résistante fournit une excellente traction et une adhérence parfaite même dans les virages et lors des manœuvres. Le dessin particulier de la bande de roulement garantit des propriétés de flottaison élevées en minimisant le compactage du sol en plus de propriétés d'autonettoyage exceptionnelles. FL 630 SUPER supporte des vitesses jusqu'à 70 km/h.

UM

US Standard

Construction



RADIAL

Machinery

Agriculture: Épandeur • Véhicule citerne • Remorque

Version	STEEL BELTED
Type	TL
Tyre Size	710/50 R 30.5
LI/SS	173 D

Dimensions US Standard

Usa code	94506293
Section Width (inch)	27
Overall Diameter (inch)	58.5
Static Loaded Radius (inch)	26.6
Rolling Circumference (inch)	179.1
Rim Rec	AG 20.00
Rim Alt	AG 24.00
ECE	E11-106R-0010340

Load capacity (lbs)

mph / psi	14	12	20	23	26	29	32	35	38	41
45	4050	4700	5360	6660	7570	8870	9920	10820	11870	13040
40	4440	5160	5870	7310	8310	9740	10890	11890	13040	14330
30	5380	6250	7110	8850	10060	11790	13180	14400	15780	17340
25	6050	7020	7990	9940	11310	13260	14810	16180	17740	19490
15	7020	8160	9290	11550	13140	15400	17220	18790	20610	22640
5	8000	9290	10580	13160	14970	17550	19610	21420	23480	25790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 06:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..