

FL 630 SUPER - Spécifications techniques



Description

FL 630 SUPER est un pneu Flotation particulièrement adapté pour les applications aux champs et sur route avec des remorques, camions-citernes et épandeurs. Sa structure résistante fournit une excellente traction et une adhérence parfaite même dans les virages et lors des manœuvres. Le dessin particulier de la bande de roulement garantit des propriétés de flottaison élevées en minimisant le compactage du sol en plus de propriétés d'autonettoyage exceptionnelles. FL 630 SUPER supporte des vitesses jusqu'à 70 km/h.

UM

International Standard

Construction



RADIAL

Machinery

Agriculture: Épandeur • Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	750/45 R 26.5
LI/SS	170 D

Dimensions International Standard

Section Width (mm)	754
Overall Diameter (mm)	1349
Static Loaded Radius (mm)	606
Rolling Circumference (mm)	4147
SRI (mm)	650
Rim Rec	AG 24.00
ECE	E4-106R-001652

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1750	1995	2240	2785	3170	3660	4150	4535	4970	5460
65	1920	2190	2460	3060	3480	4020	4560	4980	5460	6000
50	2325	2655	2980	3705	4215	4865	5520	6030	6610	7260
40	2615	2985	3350	4165	4735	5470	6205	6775	7430	8160
25	3035	3465	3890	4835	5500	6355	7205	7870	8630	9480
10	3460	3945	4430	5510	6265	7240	8210	8965	9830	10800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 02:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..