

FLOTATION 351 - Fiche de données



Description

FLOTATION 351 est un pneu diagonal Flotation idéal pour les applications de transport avec les remorques. Les crampons extra profonds fournissent une traction exceptionnelle et allongent la vie du pneu. FLOTATION 351 est le pneu idéal sur les surfaces mouillées et humides en assurant une capacité de charge élevée.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Remorque

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
42 X 25.00 - 20	STANDARD	HF3	135 B	12	20.50 HF	20.50 VF	605	1110	508	3302	TL	E11-106R-004382
42 X 25.00 - 20	STANDARD	HF3	139 B	16	20.50 HF	20.50 VF	605	1110	508	3302	TL	E11-106R-004383
48 X 25.00 - 20	STANDARD	HF3	144 B	10	20.50 HF	20.50 VF	630	1270	559	3785	TL	
48 X 31.00 - 20	STANDARD	HF3	148 B	12	26.00 HF	26.00 VF	775	1283	559	3886	TL	E11-106R-004385
66 X 43.00 - 25	STANDARD	HF3	170 B	16	36.0 TH		1020	1750	782	5213	TL	E11-106R-003346
66 X 43.00 - 25	STANDARD	HF3	150 B	6	36.0 TH		1020	1750	782	5213	TL	
66 X 43.00 - 25	STANDARD	HF3	160 B	10	36.0 TH		1020	1750	782	5213	TL	E11-106R-004378

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 03:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..