

FS 216 - Spécifications techniques



Description

FS 216 bénéficie d'un dessin robuste des crampons avec angles optimisés et plus larges pour améliorer les performances en thème de traction pour les porteurs forestiers et les débusqueuses. Ce pneu offre une excellente résistance aux coupures et déchirures même dans les conditions de service les plus critiques, assurant à tout moment un maximum de protection contre tous les éventuels dommages.

UM

International Standard

Construction

❖ BIAS

Machinery

Agriculture: Débusqueuse

| | |
|-----------|--------------|
| Version | STEEL BELTED |
| Type | TL |
| Tyre Size | 30.5L - 32 |

Dimensions International Standard

| | |
|----------------------------|---------|
| Ply Rating | 32 |
| Section Width (mm) | 775 |
| Overall Diameter (mm) | 1847 |
| Static Loaded Radius (mm) | 833 |
| Rolling Circumference (mm) | 5466 |
| Rim Rec | DH 27 |
| Rim Alt | DH 27 B |
| TRA Code | LS2 |

Load capacity (Kg)

| km/h / bar | 3.8 | 3.5 |
|------------|-------|------|
| 10 | 11500 | - |
| 30 | - | 8000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 13:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..