

GR 288 - Spécifications techniques



Description

GR 288 (G-2/L-2) est un pneu polyvalent à carcasse diagonale pour niveleuses ou chargeuses. Ce pneu est idéal pour une utilisation dans le secteur bâtiment, préparation du site, construction routière ainsi que sur les autres sols mous ou boueux. Le dessin de la bande de roulement lui confère d'excellentes propriétés d'auto-nettoyage qui se traduisent par une excellente traction. Grâce à son mélange spécial résistant aux coupures et déchirures, ce pneu a une durée de vie élevée.

UM

US Standard

Construction

✚ BIAS

Machinery

Industriel: Bulldozer • Chargeur

OTR: Niveleuse

Version	STANDARD
Type	TL
Tyre Size	20.5 - 25

Dimensions US Standard

Usa code	94035632
Ply Rating	20
Overall Width (inch)	20.5
Overall Diameter (inch)	58.3
Static Loaded Radius (inch)	25.8
Rolling Circumference (inch)	173.1
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7
ECE	E11-106R-005180
TRA Code	G2/L2
Tread Depth	36

Load capacity (lbs)

mph / psi	40	65
25	9900	-
5	-	20900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 15:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..