

## JUMBO TRAX HD - Spécifications techniques



### Description

JUMBO TRAX HD est un pneu avec dessin à blocs de la bande de roulement pour les chargeuses compactes. Ce pneu se distingue de par son extraordinaire résistance aux coupures et déchirures et il est particulièrement indiqué pour les services pénibles. La bande de roulement profonde associée à l'excellente protection des flancs garantit un long cycle de vie du pneu. JUMBO TRAX HD est aussi disponible en version spéciale.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriel: Chargeur compact

Version	IMPLEMENT
Type	TL
Tyre Size	10 - 16.5
LI/SS	120 A8

## Dimensions US Standard

Usa code	94057313
Ply Rating	10
Section Width (inch)	10.6
Overall Diameter (inch)	31.3
Static Loaded Radius (inch)	14.3
Rolling Circumference (inch)	92.3
Rim Rec	8.25
ECE	E11-106R-003523

## Load capacity (lbs)

mph / psi	75
25	3080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 18:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..