

JUMBO TRAX HD - Spécifications techniques



Description

JUMBO TRAX HD est un pneu avec dessin à blocs de la bande de roulement pour les chargeuses compactes. Ce pneu se distingue de par son extraordinaire résistance aux coupures et déchirures et il est particulièrement indiqué pour les services pénibles. La bande de roulement profonde associée à l'excellente protection des flancs garantit un long cycle de vie du pneu. JUMBO TRAX HD est aussi disponible en version spéciale.

UM

International Standard

Construction

✚ BIAS

Machinery

Industriel: Chargeur compact

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

Dimensions International Standard

Ply Rating	10
Section Width (mm)	325
Overall Diameter (mm)	855
Static Loaded Radius (mm)	387
Rolling Circumference (mm)	2522
Rim Rec	9.75
ECE	E11-106R-005563

Load capacity (Kg)

km/h / bar	4.50
10	2540
15	2005
25	1855

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 12:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..