

LG 306 - Spécifications techniques



Description

LG 306 est un pneu pour pelouses et jardins, approprié pour les faucheuses. Dans certaines tailles, LG 306 convient aussi pour les micro tracteurs. Le dessin spécifique de la bande de roulement rend le pneu délicat sur le terrain, tout en facilitant le maniement et les manœuvres. LG 306 est disponible dans une version "aramid-belted", avec ceintures en aramide, pour les utilisateurs qui ont besoin d'une plus grande résistance aux perforations.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Faucheuse • Micro tracteur

Version	ARAMID BELTED
Type	TL
Tyre Size	26 X 12.00 - 12

Dimensions International Standard

Ply Rating	8
Section Width (mm)	310
Overall Diameter (mm)	640
Static Loaded Radius (mm)	283
Rolling Circumference (mm)	1856
Rim Rec	10.50 I - 55 ; I - 70 ; I - 90
Rim Alt	10½ JA ; 8½ JA
ECE	E11-106R-005304

Load capacity (Kg)

km/h / bar	3.00
15	1250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 04:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..