

LIFTMAX LM SMOOTH - Fiche de données



Description

LIFTMAX LM SMOOTH a été spécialement conçu pour les chariots porte-conteneurs vides, mais il convient également aux élévateurs de charges lourdes et aux chariots élévateurs à fourche. Le dessin lisse de la bande de roulement assure une répartition uniforme du poids sur toute la surface de contact et évite les fissures à la base des crampons. Le mélange unique de la bande de roulement garantit une excellente usure et une longue durée de vie. LIFTMAX LM SMOOTH est parfait pour les opérations logistiques sur des surfaces dures, en particulier sur l'asphalte. La carcasse All Steel robuste et le flanc renforcé offrent une stabilité maximale et une maniabilité optimale en mode de levage. En outre, la carcasse radiale absorbe les irrégularités de la surface, ce qui améliore le confort de conduite et réduit la fatigue de l'opérateur. Conforme aux normes antistatiques, LIFTMAX LM SMOOTH est capable de dissiper la charge statique du véhicule.

UM

US Standard

Construction



RADIAL

Machinery

Industriel: Chariot porte-conteneur • Chariot élévateur

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	Type
14.00 R 24	INDUSTRIAL	94513246	193 A5	10.00W	10.0, 10.00WA	15.3	55.7	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 09:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..