

LOADER SPECIAL - Spécifications techniques



Description

LOADER SPECIAL L-5 est un pneu à structure diagonale qui garde vos chargeuses en mouvement en leur assurant une excellente efficacité dans les opérations pénibles sur les terrains rocheux. L'excellente traction et la résistance exceptionnelle aux coupures vous aideront à améliorer votre productivité.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Bulldozer • Chargeur

Version	STEEL BELTED
Type	TL
Tyre Size	45/65 - 45

Dimensions US Standard

Usa code	94056903
Ply Rating	58
Overall Width (inch)	46.7
Overall Diameter (inch)	109.6
Rim Rec	36.00/4.5
TRA Code	L5
Tread Depth	146

Load capacity (lbs)

mph / psi	98
5	110000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 14:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..