

LT TR 182 - Spécifications techniques



Description

LT TR 182 convient pour les opérations de transports avec véhicules utilitaires légers. Ce pneu à haute vitesse est utilisé essentiellement sur route et il réduit considérablement la consommation de carburant. De plus, le pneu LT TR 182 est facile à monter.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Camion léger

Version	STANDARD
Type	TL
Tyre Size	8 - 14.5

Dimensions International Standard

Ply Rating	14
Section Width (mm)	207
Overall Diameter (mm)	710
Rim Rec	6.00 MH

Load capacity (Kg)

km/h / bar	7.90
100 LS	1375
100 LD	1210

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 21:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..