

LT TR 182 - Spécifications techniques



Description

LT TR 182 convient pour les opérations de transports avec véhicules utilitaires légers. Ce pneu à haute vitesse est utilisé essentiellement sur route et il réduit considérablement la consommation de carburant. De plus, le pneu LT TR 182 est facile à monter.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Camion léger

Version	STANDARD
Type	TL
Tyre Size	8 - 14.5

Dimensions US Standard

Usa code	94027927
Ply Rating	14
Section Width (inch)	8.1
Overall Diameter (inch)	28
Rim Rec	6.00 MH

Load capacity (lbs)

mph / psi	115
62 LS	3030
62 LD	2665

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 17:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..