

## LUG STAR - Spécifications techniques



### Description

LUG STAR est un pneu industriel conçu pour les applications voies-route avec des pelleteuses qui demandent une excellente traction. Le pneu est caractérisé par des qualités exceptionnelles d'auto-nettoyage et un mélange de la bande de roulement particulièrement résistant aux coupures. La carcasse robuste offre une excellente durabilité.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriel: Engin rail-route

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20

## Dimensions International Standard

<b>Ply Rating</b>	18
<b>Overall Width (mm)</b>	280
<b>Overall Diameter (mm)</b>	1080
<b>Static Loaded Radius (mm)</b>	506
<b>Rolling Circumference (mm)</b>	3343
<b>Rim Rec</b>	7.5
<b>Rim Alt</b>	7.0 ; 8.0

## Load capacity (Kg)

	km/h / bar	10.00
	10	6890
	25	5300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 05:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..