

## MH TR 182 - Spécifications techniques



### Description

MH TR 182 convient pour les véhicules qui transportent des mobil-homes. Ce pneu à haute vitesse utilisé essentiellement sur route permet de réaliser d'importantes économies de carburant. MH TR 182 assure un long cycle de vie du pneu et des performances élevées toute sa vie durant.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Mobil Home

|           |          |
|-----------|----------|
| Version   | STANDARD |
| Type      | TL       |
| Tyre Size | 8 - 14.5 |

## Dimensions International Standard

|                              |         |
|------------------------------|---------|
| <b>Ply Rating</b>            | 12      |
| <b>Section Width (mm)</b>    | 207     |
| <b>Overall Diameter (mm)</b> | 710     |
| <b>Rim Rec</b>               | 6.00 MH |

## Load capacity (Kg)

| km/h / bar | 6.90 |
|------------|------|
| 100        | 1285 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 07:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..