

MH TR 182 - Fiche de données



Description

MH TR 182 convient pour les véhicules qui transportent des mobil-homes. Ce pneu à haute vitesse utilisé essentiellement sur route permet de réaliser d'importantes économies de carburant. MH TR 182 assure un long cycle de vie du pneu et des performances élevées toute sa vie durant.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Mobil Home

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type
8 - 14.5	STANDARD	14	6.00 MH		207	710	TL
8 - 14.5	STANDARD	8	6.00 MH		207	710	TL
8 - 14.5	STANDARD	10	6.00 MH		207	710	TL
8 - 14.5	STANDARD	12	6.00 MH		207	710	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 07:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..