

MP 570 - Spécifications techniques



Description

MP 570 est un pneu agro-industriel pour une utilisation essentiellement sur route, approprié pour les excavatrices et les chargeuses compactes. Ce pneu assure une traction optimale et présente d'excellentes qualités d'auto-nettoyage dans n'importe quelles conditions de fonctionnement.

UM

US Standard

Construction

❖ BIAS

Machinery

Agriculture: Chargeuse-pelleteuse

Industriel: Chargeuse-pelleteuse • Pelleteuse • Véhicule universel

Version	STANDARD
Type	TL
Tyre Size	12.5 - 18

Dimensions US Standard

Usa code	94015214
Ply Rating	12
Section Width (inch)	12.1
Overall Diameter (inch)	39
Static Loaded Radius (inch)	17.7
Rolling Circumference (inch)	116.1
Rim Rec	11
Rim Alt	12 SDC

Load capacity (lbs)

mph / psi	51
50	4480
30	4810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 12:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..