

MP 570 - Spécifications techniques



Description

MP 570 est un pneu agro-industriel pour une utilisation essentiellement sur route, approprié pour les excavatrices et les chargeuses compactes. Ce pneu assure une traction optimale et présente d'excellentes qualités d'auto-nettoyage dans n'importe quelles conditions de fonctionnement.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Chargeuse-pelleteuse

Industriel: Chargeuse-pelleteuse • Pelleteuse • Véhicule universel

Version	STANDARD
Type	TL
Tyre Size	12.5 - 20

Dimensions International Standard

Ply Rating	10
Section Width (mm)	335
Overall Diameter (mm)	1050
Static Loaded Radius (mm)	480
Rolling Circumference (mm)	3130
Rim Rec	11
Rim Alt	12 SDC

Load capacity (Kg)

km/h / bar	3.00
80	1850
50	2065

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..