

MP 570 - Fiche de données



Description

MP 570 est un pneu agro-industriel pour une utilisation essentiellement sur route, approprié pour les excavatrices et les chargeuses compactes. Ce pneu assure une traction optimale et présente d'excellentes qualités d'auto-nettoyage dans n'importe quelles conditions de fonctionnement.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Chargeuse-pelleteuse

Industriel: Chargeuse-pelleteuse • Pelleteuse • Véhicule universel

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
12.5 - 18	STANDARD	94015214	12	11	12 SDC	12.1	39	17.7	116.1	TL	
12.5 - 18	STANDARD	94038312	10	11	12 SDC	12.1	39	17.7	116.1	TL	E4-54R-0022629
12.5 - 20	STANDARD	94038329	12	11	12 SDC	13.2	41.3	18.9	123.2	TL	E4-54R-0022634
12.5 - 20	STANDARD	94015238	10	11	12 SDC	13.2	41.3	18.9	123.2	TL	
14.5 - 20	STANDARD	94015252	12	11	12 SDC	14.2	43.9	19.9	130.9	TL	E11-106R-005342

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 15:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..