

MP 585 - Spécifications techniques



Description

MP 585 est un pneu agro-industriel adapté pour des véhicules polyvalents dans les applications de services municipaux de voirie. Ce pneu a été spécialement conçu avec un dessin de la bande de roulement à blocs qui offre un maximum de stabilité et durabilité dans les conditions de travail les plus difficiles même que à des vitesses élevées.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Véhicule universel

Industriel: Véhicule universel

Version	STANDARD
Type	TT
Tyre Size	6.50 - 20
LI/SS	38 A8

Dimensions US Standard

Usa code	94051243
Ply Rating	10
Section Width (inch)	7.9
Overall Diameter (inch)	34.4
Rim Rec	5.50 F
Rim Alt	4.00 E ; 5.00 F
ECE	E11-106R-004308

Load capacity (lbs)

mph / psi	80
25	1650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 05:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..